



Sun Fire™ X4440 Server

Ultimate performance, scalability, and power efficiency in a two rack-unit system



Highlights

- The highest performance and memory capacity, and twice the networking connectivity
- Hardware and cross-platform virtualization — plus VMware support — enable server consolidation and help you save on equipment costs
- Next-generation AMD Opteron processors™ ensure high bandwidth for simultaneous 32-bit and 64-bit application multitasking
- Integrated Lights Out Manager (ILOM) makes remote management simple from anywhere in the world
- Redundant, hot-swappable power supplies, fans, and disk drives improve reliability, while making replacement exceedingly simple
- Runs the Solaris™, Red Hat Enterprise Linux, SUSE Linux, Windows, and VMware operating systems
- Optional professional services, training, and integrated support to optimize your server implementation



Sun is revolutionizing the industry with a powerful, scalable, energy-efficient server designed to support escalating business and IT growth without increasing operational expenses. The Sun Fire™ X4440 server features blazingly fast AMD Opteron processors, huge storage and memory capacity, numerous connectivity options, and massive room for expansion. This 64-bit, two rack-unit (2 RU) system delivers the highest performance and scalability in its class, offering a solid foundation for rapidly rising datacenter requirements, while incorporating software tools to streamline administration and advanced features to minimize resource costs.

The speed and capacity for tomorrow's applications

The Sun Fire X4440 server provides unparalleled speed and system density, plus exceptional connectivity, power-saving, virtualization, and management features, making it an ideal solution for server consolidation, database services, Web 2.0 infrastructure, and high-performance/grid computing. Leveraging its versatility, you can easily run today's 32-bit operations as you implement next-generation 64-bit applications.

The Sun Fire X4440 server is the world's most compact four-socket, x64 platform capable of housing up to four dual-core AMD Opteron processors, 1.1 TB of internal storage, 128 GB of memory, and twice the networking

connectivity in a chassis half the size of competing products. Its superior scalability ensures the server will meet tomorrow's business and IT requirements without the need for additional equipment, while its compact form factor minimizes space requirements and the need for scarce datacenter real estate.

Sun offers a suite of services to optimize your Sun Fire X4440 server implementation. The combined system and support pricing is often less than the traditional cost of purchasing the items as separate and individual components. Sun can also help you fast-track your consolidation and virtualization initiatives with solutions that help reduce IT costs, improve availability and utilization, and simplify infrastructure management.

Sun Fire X4440 Server Specifications

Architecture

Processor

- Two or four dual-core AMD Opteron processors

Cache

- 1 MB per dual-core processor

Main memory

- 32 DDR2 DIMM slots (eight DIMM slots per CPU socket); system supports 4 GB (4x 1 GB) to 128 GB (32x 4 GB) of memory

Mass storage and media

- Eight hot-swappable 2.5-in. SAS disk drives with optional SAS host bus adapter (HBA)
- One EIDE DVD±RW drive (optional)

RAID configuration

- Add-on RAID 0, 1, IE, 5, 5EE, 6, 10, 50, 60 with SAS RAID HBA

Standard/integrated interfaces

- Network: Four 10/100/1000 Base-T Ethernet ports
- Network management: One dedicated 10/100 Base-T Ethernet port
- Serial: One TIA/EIA-232-F asynchronous RJ45 connector
- SAS: Two four-channel SAS interfaces, internal access only
- USB: Five USB 2.0 ports (two front, two rear, one internal)
- Expansion slots: Six MD2 low-profile PCI Express slots (1x 16-lane, 4x 8-lane, 1x 4-lane)

Software

Operating systems

- Solaris 10 Operating System
- Red Hat Enterprise Linux 4
- Red Hat Enterprise Linux 5
- SUSE Linux Enterprise Server 10 (64-bit)
- VMware ESX 3.0.2
- Windows 2003 Standard and Enterprise versions (32-bit and 64-bit)¹

¹ Supported editions include Windows Server 2003 SP1, R2, SP2, R2 with SP2

Languages

- C/C++, FORTRAN
- Java™ programming language
- All other standard Sun-supported languages

Networking

- ONC™, ONC+™, NFS, WebNFS™, TCP/IP, Sun-Link™, OSI, MHS, IPX™/SPX, SMB technologies, and XML

Management

- CLI (in-band and out-of-band), IPMI 2.0 (in-band and out-of-band), SNMP (out-of-band only)

Environment

AC power

- 90–264 V AC (47–63 Hz)

Operating temperature/humidity (single nonrack system)

- 5° C to 35° C (41° F to 95° F), 10–90% relative humidity, noncondensing

Nonoperating temperature/humidity (single, nonrack system)

- -40° C to 70° C (-40° F to 158° F), up to 93% relative humidity, noncondensing

Operating altitude (single nonrack system)

- Up to 3,048m, maximum ambient temperature is derated by 1° C per 300m above 900m

Nonoperating altitude (single nonrack system)

- 15 kPa

Acoustic noise (single nonrack system)

- LwAd: At max. ambient, 7 dB
- LpAm bystander: At max. ambient, 56 dB

Optional

- Cable management arm
- Toolless rackmount slide rail kit

Learn More

For more information on the Sun Fire X4440 server, go to: sun.com/x4440.

Try risk-free for 60 days:
Apply for a free trial at sun.com/tryandbuy.

Power

- Dual-redundant, hot-swappable power supply
- UL maximum input power: 8.2 A RMS at 100 V AC
- Power supply output rating: 650 W

Regulations (meets or exceeds)

- Safety: IEC 60950, UL/CSA 60950, EN 60950, CB Scheme with all country differences
- RFI/EMI: FCC CFR 47 Part 15 Class A, EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 300-386
- Immunity: EN55024, EN300-386

Certifications

- Safety: UL/cUL, UL DEMKO, CE, BSMI, CCC, GOST-R, S-Mark
- EMC: CE, FCC, VCCI, ICES, C-Tick, MIC, CCC, GOST-R, BSMI Class A
- Other: Complies with WEEE Directive (2002/96/EC) and RoHS Directive (2002/95/EC)

Dimensions and weight

Height	87.85mm (3.46 in.)
Width	425.5mm (16.75 in.)
Depth	711.2mm (28 in.)
Weight	28.6. kg (63 lbs.) min.

Warranty

- Three years, next business day

